

SMX 131R-4/2

SMXSERIES » Modular » Central expansion » I/O module

BBH
PRODUCTS



DESCRIPTION

Central I/O extension module for
SMX_{MODULAR} - basic modules

- 12 Digital inputs
- 4 Relay outputs
- 6 Digital I/Os
- 2 Auxiliary / pulse outputs
- Safety controller up to PL e acc. to EN ISO 13849-1
or SIL3 acc. to IEC 61508

CHARACTERISTIC OF THE MODULE

- » Pulse outputs for cross-circuit detection of digital input signals
- » External contact monitoring of connected switchgear (EMU)
- » Comprehensive diagnostic functions integrated

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

www.bbh-products.de

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

contact@bbh-products.de

SAFETY @ ITS BEST!

SMX 131R-4/2

SMX_{SERIES} » Modular » Central expansion » I/O module

SAFETY RELATED CHARACTERISTIC DATA

Performance Level	PL e (EN ISO 13849-1)
PFH ¹⁾ / architecture	9,2 FIT / Cat. 4 ¹⁾
	1-channel per Rel 20 FIT (max.8)
	2-channel per Rel 1,0 FIT (max.4)
Safety Integrity Level	SIL 3 (IEC 61508)
Proof test interval	20 years = max. operating period

GENERAL DATA

Max. no. of expansion modules	–
Interface for expansion modules	T-bus connector, pluggable in top-hat rail
Number of safe digital inputs	12
Number of safe digital outputs	
	pp-switching ** 4
	pn-switching ** 2
Number of safe digital I/O	6
Number of relay outputs	4
Number of safe analogue inputs	–
Number of auxiliary outputs	2
Number of pulse outputs (clock outputs)	2
Type of connection	Plug-in terminals with spring or screw connection
Axis monitoring (Axes / Encoder interfaces)	–
Encoder interfaces (D-Sub / screw terminals)	–

** pn/pp configurable via SafePLC

¹⁾ Value applies only for extension module. For total assessment in accordance with EN ISO 13849-1 one must use a series the corresponding basic device => $PFH_{Logic} = PFH_{Basic} + PFH_{Extension}$

SMX 131R-4/2

SMXSERIES » Modular » Central expansion » I/O module

ELECTRICAL DATA

Supply voltage (tolerance)		24 VDC; 2A (-15%, +20%)	
Fuse	X11.1	min. 30 VDC; max. 10A	
Max. Power consumption (logic)			
	SMX131R-4/2	3 W	
Rated data digital inputs		24 VDC; 20 mA, Typ1 acc. to IEC 61131-2	
Rated data digital outputs			
	pn-switching	24 VDC; 2A *	
	pp-switching	24 VDC; 2A *	
	Auxiliary outputs	24 VDC; 250mA	
	Pulse outputs (clock outputs)	24 VDC; 250mA	
	Digital I/O	01 - 05	24 VDC; 0,5A
		06 - 10	24 VDC; 2A
Rated data relays			
	Normally open	DC 13	24 VDC; 2A
		AC 15	230 VAC; 2A
	Normally closed (Read back contact)	DC 13	24 VDC; 2A

* see „Derating outputs“

DERATING OUTPUTS

- » Maximum current load based on temperature.
- » The maximum total current is 10A.

type of module	outputs	temperature 30°C / 50°C
SMX131R-4/2/x	IQx6	2A / 1,8A

SMX 131R-4/2

SMXSERIES » Modular » Central expansion » I/O module

BBH
PRODUCTS

ENVIRONMENTAL DATA

Temperature	0°C ... +50°C operation -25°C ... +70°C storage and transport
Class of protection	IP 20
Climatic category	3K3 acc. to DIN EN 60721-3
Min-, Maximum relative humidity (no condensation)	5% - 85%
EMC	DIN EN 61000-6-2, DIN EN 61000-6-4, DIN EN 61000-6-7, DIN EN 61800-3, DIN EN 61326-3, DIN EN 62061
Operating altitude	2000m

MECHANICAL DATA

Dimension (HxDxW [mm])	SMX131R-4/2	100x115x67,5
Weight [g]	SMX131R-4/2	545
Mounting		to snap on top-hat rail
Number of T-Bus		
	SMX131R-4/2	3
Min. terminal cross-section / AWG		0,2 mm ² / 24
Max. terminal cross-section / AWG		2,5 mm ² / 12

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

www.bbh-products.de

contact@bbh-products.de

SAFETY @ ITS BEST!

SMX 131R-4/2

SMXSERIES » Modular » Central expansion » I/O module

BBH
PRODUCTS

X 19		
Pin	1 - Q1.1	Sicherer Relaisausgang 1
	2 - Q1.2	
	3 - Q2.1	Sicherer Relaisausgang 2
	4 - Q2.2	
X 20		
Pin	1 - 3.1	Sicherer Relaisausgang 3
	2 - 3.2	
	3 - 4.1	Sicherer Relaisausgang 4
	4 - 4.2	
X 21		
Pin	1 - IQ03	Safe digital inputs, outputs pp-switching
	2 - IQ04	
	3 - IQ05	
	4 - IQ06	

X 23		
Pin	1 - I05	Safe digital inputs
	2 - I06	
	3 - I07	
	4 - I08	
X24		
Pin	1 - I09	Safe digital inputs
	2 - I10	
	3 - I11	
	4 - I12	

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

www.bbh-products.de

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

contact@bbh-products.de

SAFETY @ ITS BEST!

SMX 131R-4/2

SMXSERIES » Modular » Central expansion » I/O module



ORDER INFORMATION

EXTENSIONS

item	description	item no.
SMX131R-4/2	I/O expansion module with relay option	2232

ACCESSORIES

item	description	item no.
SXxxx-x	Terminal connector, screw terminals (set), encoded for cabling SMX131R/2	on request
SXxxx-x	Terminal connector, spring terminals (set), encoded for cabling SMX131R/2	on request
SX0000-9	T-Bus connector voltage-carrying (grey)	1015

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

www.bbh-products.de

contact@bbh-products.de

SAFETY @ ITS BEST!