


SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes module

BBH
PRODUCTS



DESCRIPTION

Decentral axis extension module for safe speed and position of up to 2 axes for further evaluation in SMX_{MODULAR} - basic modules and with extended encoder functionality

- 14 Digital inputs
- 8 Encoder interfaces
- 2 Analogue inputs *
- 2 Relay outputs
- 2 Auxiliary / pulse outputs
- 2 / 4 pn- or pp-switching outputs
- Safety controller up to PL e acc. to EN ISO 13849-1 or SIL3 acc. to IEC 61508

CHARACTERISTIC OF THE MODULE

- » Decentralised axis expansion module
 - Decentralised: Communication with base module SMX100-x via communication interface (/D)
 - Central: Communication with base module SMX 100-x via backplane bus
- » Safe detection of speed and position of one or two axes
- » Movement monitoring of one or two axes up to PL e EN ISO 13849-1 or SIL 3 acc. to IEC 61508
- » Speed monitoring:
- » RPM-monitoring
- » Standstill monitoring
- » Sense of rotation monitoring
- » Safe incremental dimension
- » Emergency Stop monitoring
- » Position monitoring
- » Position range monitoring
- » Trend range monitoring
- » Target position monitoring
- » Logic diagram oriented programming via SafePLC²
- » Pulse outputs for cross-shortening detection of digital input signals
- » External contact monitoring of connected switchgear (EMU)
- » Switchable safe semi-conductor outputs pn-, pp- switching for safety-relevant functions
- » Monitored relay outputs for safety relevant functions
- » Comprehensive diagnostics functions integrated
- » Parameter management for expansion modules in base device
- » Coded status display via front-side 7 segment display and status LEDs
- » Extended functionality:
 - Allows the connection of 2 rotary encoders per axis (SSI-Absolut, SinCos, Incremental-TTL, HTL-proximity sensor)
 - 2nd encoder interface also supports HTL (200 kHz), Sin/Cos High-Resolution and Resolver

* = see "general data"

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

www.bbh-products.de

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

contact@bbh-products.de

SAFETY @ ITS BEST!

SMX 112-2A/2/D

SMX_{SERIES} » Modular » Decentral expansion » 2 Axes module

SAFETY RELATED CHARACTERISTIC DATA

Performance Level	PL e (EN ISO 13849-1)
PFH ¹⁾ / architecture	12,6 FIT / Cat 4
Safety Integrity Level	SIL 3 (IEC 61508)
Proof test interval	20 years = max. operating period

GENERAL DATA

Max. no. of expansion modules	–
Interface for expansion modules	Communication interface (/D) or T-bus connector, pluggable in top-hat rail, RJ-45 (Ethernet)
Number of safe digital inputs	14
Number of safe digital outputs	
pp-switching **	4
pn-switching **	2
Number of safe digital I/O	–
Number of relay outputs	2
Number of safe analogue inputs	2 ***
Number of auxiliary outputs	2
Number of pulse outputs (clock outputs)	2
Type of connection	Plug-in terminals with spring or screw connection
Axis monitoring	2
Encoder interfaces (D-Sub / screw terminals)	4 / 4 **
Encoder technology (See table Encoder specifications)	D-SUB X31 / X32: SSI-Absolut, SinCos, Incremental-TTL D-SUB X33 / X34: SSI-Absolut, SinCos, SinCos (HighRes), Resolver Terminal X23: HTL-proximity sensor (10 kHz), Terminals X27, X28, X29, X30: Incremental-HTL (200 kHz)

* Maximum 2 Encoder / Axis

** pn/pp are configurable via SafePLC²

*** Analogue current, voltage inputs are available as options

SMX112-2A-U (/2) Voltage inputs

SMX112-2A-I (/2) Current inputs

SMX112-2A (/2) Voltage inputs (X25) and current inputs (X26)

¹⁾ Value applies only for extension module. For total assessment in accordance with EN ISO 13849-1 one must use a series connection with the corresponding basic device => $PFH_{Logic} = PFH_{Basic} + PFH_{Extension}$

SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes module

ELECTRICAL DATA

Supply voltage (tolerance)		24 VDC; 2A (-15%, +20%)
Fuse	X11.1	min. 30 VDC; max. 3,15A
	X11.2	min. 30 VDC; max. 10A
Max. Power consumption (logic)		
	SMX112-2A/2/D	5,4 W
Rated data digital inputs		24 VDC; 20 mA Typ1 acc. to IEC 61131-2
Rated data digital outputs		
	pn-switching	24 VDC; 2A *
	pp-switching	24 VDC; 2A *
	auxiliary outputs	24 VDC; 250mA
	pulse outputs (clock outputs)	24 VDC; 250mA
Rated data relays		
	Normally open	
	DC 13	24 VDC; 2A
	AC 15	230 VAC; 2A
Rated data analogue inputs		
	SMX112-2A/2/D	-7 ... +10 V 4 ... 20 mA

* see „Derating outputs“

DERATING OUTPUTS

- » Maximum current load based on temperature.
- » The maximum total current is 10A.

type of module	outputs	temperature 30°C / 50°C
SMX1xx/2/x	Q 1 – Q 4	2A / 1,8A

SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes module

BBH
PRODUCTS

ENVIRONMENTAL DATA

Temperature	0°C ... +50°C operation -25°C ... +70°C storage and transport
Class of protection	IP 20
Climatic category	3K3 acc. to DIN EN 60721-3
Min-, Maximum relative humidity (no condensation)	5% - 85%
EMC	DIN EN 61000-6-2, DIN EN 61000-6-4, DIN EN 61000-6-7, DIN EN 61800-3, DIN EN 61326-3, DIN EN 62061
Operating altitude	2000m

MECHANICAL DATA

Dimension (HxDxW [mm])	SMX112-2A/2/D	100x115x135
Weight [g]	SMX112-2A/2/D	620
Mounting	to snap on top-hat rail	
Number of T-Bus	6	
Min. terminal cross-section / AWG	0,2 mm ² / 24	
Max. terminal cross-section / AWG	2,5 mm ² / 12	

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

www.bbh-products.de

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35


contact@bbh-products.de

SAFETY @ ITS BEST!

SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes modular

DEVICE INTERFACES



Interface	Description of interface
X11 – X14 / X17 – X26	Voltage supply and I/O interface
X91 / X92	Decentralised SDDC ETH and SMMC interface
X31 / X32 / X33 / X34	Encoder interfaces *
X23 / X27 - X30	Encoder interfaces *

VOLTAGE SUPPLY AND I/O INTERFACE

X 11		
Pin	1 - A1.1	Voltage supply device +24 VDC
	2 - A1.2	Voltage supply device +24 VDC outputs
	3 - A2.1	Voltage supply device 0 VDC
	4 - A2.2	Voltage supply device 0 VDC
X 12		
Pin	1 - I13	Safe digital inputs
	2 - I14	
	3 - T1	Clock outputs
	4 - T2	

X 13		
Pin	1 – UE1+	Voltage supply Encoder +24V DC X31
	2 – UE1-	Voltage supply Encoder 0V DC X31
	3 - Y1	Auxiliary outputs
	4 - Y2	
X 14		
Pin	1 - I01	Safe digital inputs
	2 - I02	
	3 - I03	
	4 - I04	

SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes modula

X 15		
Pin	1 - UE2+	Voltage supply Encoder +24V DC X32
	2 - UE2-	Voltage supply Encoder 0V DC X32
	3 - NC	No functions
	4 - NC	
X17		
Pin	1 - UE3+	Voltage supply Encoder +24V DC X33
	2 - UE3-	Voltage supply Encoder 0V DC X33
	3 - UR3	Reference voltage Encoder X33
	4 - NC	No function
X19		
Pin	1 - UE4+	Voltage supply Encoder +24V DC X34
	2 - UE4-	Voltage supply Encoder 0V DC X34
	3 - UR4	Reference voltage Encoder X34
	4 - NC	No function
X21		
Pin	1 - Q1	Output of the pn-switching Q1_PP / pp-switching Q1
	2 - Q2	Output of the pn-switching Q2_PN / pp-switching Q2
	3 - Q3	Output of the pn-switching Q3_PP / pp-switching Q3
	4 - Q4	Output of the pn-switching Q4_PN / pp-switching Q4

X22		
Pin	1 - Q5.1	Safe relay output
	2 - Q5.2	
	3 - Q6.1	Safe relay output
	4 - Q6.2	
X 23		
Pin	1 - I05	Safe digital inputs
	2 - I06	
	3 - I07	
	4 - I08	
X 24		
Pin	1 - I09	Safe digital inputs
	2 - I10	
	3 - I11	
	4 - I12	
X25 (voltage inputs)		
Pin	1 - AIN 1+	Safe analogue inputs
	2 - AIN 1-	
	3 - AIN 2+	Safe analogue inputs
	4 - AIN 2-	
X26 (current inputs)		
Pin	1 - AIN 3+	Safe analogue inputs
	2 - AIN 3-	
	3 - AIN 4+	Safe analogue inputs
	4 - AIN 4-	

DECENTRALISED SDDC ETH AND SMMC INTERFACE

Pin assignment female connector

Communication interface (RJ45)				Front side SMX
Pin	Name	Description	Colour	X91 / X92
1	TX+	Transmit Data +	white-orange	
2	TX-	Transmit Data -	orange	
3	RX+	Receive Data +	white-green	
4	nc	not used	blue	
5	nc	not used	white-blue	
6	RX-	Receive Data -	green	
7	nc	not used	white-brown	
8	nc	not used	brown	

Safe Master – Master Communication (SMMC)

SMMC communication enable a safe data exchange of 2 bytes between multiple SDDC masters. Communication takes place without a master for coordinating the data. This means that data exchange between available subscribers is always possible. This principle means that an incomplete or separates network can work in part areas without changing the configuration.

Each port can be configured in the SafePLC².

INTEGRATED COMMUNICATION INTERFACE

General data

Decentralised communication interface

/D

2x RJ 45 *

* optional for SDDC or SMMC

ENCODER INTERFACES

Pin assignment X31 / X32 , X33 / X34

Pin	X31 / X32 Inc / Sin/Cos / SSI	X33 / X34 Inc / Sin/Cos / SSI	X33 / X34 Resolver	Front side SMX
1	n.c.	n.c.	Ref_Out +	
2	GND_ENC	GND_ENC	GND_ENC	
3	n.c.	n.c. / n.c. / Clk +	Ref_In +	
4	B- / COS - / Clk -	B- / COS - / n.c.	COS -	
5	A+ / SIN + / Data +	A+ / SIN + / Data +	SIN +	
6	A- / SIN - / Data -	A- / SIN - / Data -	SIN -	
7	n.c.	n.c. / n.c. / Clk -	Ref -	
8	B+ / COS + / Clk +	B+ / COS + / n.c.	COS +	
9	U_ENC	U_ENC	U_ENC	

Pin assignment X23 , X27 / X28 , X29 / X30

Pin	Z1 – Z1 / Z2 – Z2	Terminals
1	A (\bar{A}) / A (\bar{A})	
2	-- / B (\bar{B})	
3	A (\bar{A}) / A (\bar{A})	
4	-- / B (\bar{B})	

Pin	A+/A-	A+ Signal	
1 – H1A	A+	24V	
2 – H2A	A-	A	
3 – H3A	A+	GND	
4 – NC	—	—	

Pin	B+/B-	B+ Signal	
1 – H1B	B+	24V	
2 – H2B	B-	B	
3 – H3B	B+	GND	
4 – NC	—	—	

ENCODER SPECIFICATIONS

Incremental - TTL	
Physical Layer	RS-422 compatible
Measuring signal A/B	Track with 90° phase difference
Type of connection	D-SUB 9pole
Max. frequency of input cycles (X31, X32 / X33, X34)	200 kHz / 250 kHz
Sin/Cos	
Physical Layer	RS-422 compatible
Measuring signal A/B	Track with 90° phase difference
Type of connection	D-SUB 9pole
Standard Mode	
Max. frequency of input clock pulse (X31, X32 / X33, X34)	200 kHz / 250 kHz
High Resolution Mode	
Max. frequency of input clock pulse (X33, X34)	15 kHz
SSI-Absolut	
Data interface	Serial Synchronous Interface (SSI) with variable data length of 12 – 28 Bit
Data format	Binary, Gray code

SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes modula

BBH
PRODUCTS

Physical Layer	RS-422 compatible
Type of connection	D-SUB 9pole
Mode	Master or Listener
SSI-Master operation	
Clock rate	150 kHz
SSI-Listener operation	
Clock rate (X31, X32 / X33, X34)	100 kHz ... 200 kHz / 100 kHz ... 250 kHz
Min. clock pause time	150 µsec
Max. clock pause time	1 msec

Resolver

Measuring signal	Sin/Cos – track with 90° phase difference
Signal frequency	max. 600 Hz (900 Hz Deep pass)
Input voltage	max. 8 Vss (an 16 kΩ)
Resolution	9 Bit / pole
Supported pole number	2 - 16
Type of connection (X33, X34)	D-SUB 9-pole
Mode	Master or Listener
Resolver-Master operation	
Reference frequency	8 kHz
Resolver-Listener operation	
Reference frequency	4 kHz – 16 kHz
Reference amplitude	8 Vss – 28 Vss
Reference signal form	Sinusoidal, triangle
Transformation ratio	2:1; 3:1; 4:1
Phase fault	max. 8°

Incremental - HTL

Signal level	24V / 0V
Physical Layer	PUSH / PULL
Max. counting pulse frequency	200 kHz
Type of connection (X27 / X28)	Plug-in terminals with spring or screw connection

HTL proximity sensor

Signal level	24V / 0V
Max. counting pulse frequency (circuit logic de-bounced)	10 kHz
Pulse width	50 µsec
Type of connection (X23)	Plug-in terminals with spring or screw connection

HTL proximity switch - extended monitoring

Signal level	24V / 0V
Max. counting frequency (circuit logic de-bounced)	4 kHz
Physical Layer	PUSH / PULL
Measuring signal A/B	Track with 90° phase difference
Type of connection (X23)	Plug-in terminals with spring or screw connection

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

www.bbh-products.de

contact@bbh-products.de

SAFETY @ ITS BEST!

SMX 112-2A/2/D

SMXSERIES » Modular » Decentral expansion » 2 Axes module



ORDER INFORMATION

EXTENSIONS

item	description	item no.
SMX 112-2A/2/D	Decentral Axis extension module for up to 2 axes with extended encoder functionality + analog option (voltage + current inputs)	2231
SMX 112-2A-I/2/D	Decentral Axis extension module for up to 2 axes with extended encoder functionality + analog option (current inputs)	2315
SMX 112-2A-U/2/D	Decentral Axis extension module for up to 2 axes with extended encoder functionality + analog option (voltage inputs)	2316

ACCESSORIES

item	description	item no.
FSOE License	Fieldbus license for FSoE	2366
SXXXX-X	Terminal connector, screw terminals (set), encoded for cabling SMX112-2A/2/D	on request
SXXXX-X	Terminal connector, spring terminals (set), encoded for cabling SMX112-2A/2/D	on request
SX0000-9	T-Bus connector voltage-carrying (grey)	1015

BBH PRODUCTS GMBH

Böttgerstraße 40
D- 92637 Weiden

www.bbh-products.de

Tel.: + 49 961/4 82 44-0
Fax: + 49 961/4 82 44-35

contact@bbh-products.de

SAFETY @ ITS BEST!